

SAFETY DATA SHEET: FRYPOWDER

SECTION 1. IDENTIFICATION OF THE PRODUCT AND COMPANY:

PRODUCT NAME	FRYPOWDER
PRODUCT USE	PROCESSING AID, FRYING OIL STABILIZER
MANUFACTURER'S NAME	OIL PROCESS SYSTEMS INC.
STREET ADDRESS	602 NORTH TACOMA STREET,
CITY	ALLENTOWN, PA 18109, USA
TEL. EMERGENCY: 610 437 4618, GENERAL INFO: 1 800 523-9844	

SECTION 2. HAZARDS IDENTIFICATION

Route of entry:	Skin contact X	Skin absorption X	Eye contact X	Inhalation X	IngestionX
This product contains citric acid and perlite mineral.					
Citric acid is a natural compound easily metabolized by humans and most living organisms. Generally Recognized as Safe substance by US FDA, can be irritant to eyes.					
Perlite has been classified as GRAS by US FDA and as Food compatible mineral by Food Chemical Codex. The mineral is flame expanded by the proprietary process. OSHA considers perlite to be a nuisance dust. Inhalation of high amounts over long periods of nuisance dust may overload lung clearance mechanism, and make the lungs more vulnerable to the respiratory diseases. Perlite may contain traces of crystalline silica (less than 0.05% if any). Long term inhalation of crystalline silica dust may cause lung cancer. Crystalline silica has been classified as a probable human carcinogen (Group 2A) by IARC, a unit of the World Health Organization. To the best of our knowledge perlite mineral used to make Frypowder does not contain crystalline silica.					
WHMIS symbols: not regulated					
Potential health effects:					
Skin: perlite is not absorbed by the skin; citric acid might be absorbed by the skin. Product can cause slight, temporary irritation of the skin and dryness if prolonged exposure.					
Eye: citric acid is irritating to eyes; perlite may also cause slight irritation (tear production and redness). Product can cause irritation if gets in eye.					
Inhalation: Pre-existing upper respiratory and lung disease might be aggravated. Acute inhalation can cause dryness of the nasal passage and lung congestion, coughing and general throat irritation. Chronic inhalation of dust should be avoided.					
Ingestion: Ingestion of small to moderate quantities is not considered harmful, but may cause irritation of the mouth, throat and stomach.					

SECTION 3. COMPOSITION/INFORMATION OF INGREDIENTS

Hazardous Ingredients	%	CAS Number	LD ₅₀ of Ingredient	OSHA PEL (mg/m ³)	ACGIH TLV (mg/m ³)	EEC (EINCS) No.
Perlite	<95	130885-09-5	Not available	10	15	
Silica	<0.05	14808-60-7	Not available	Not available	0.05	
Citric acid	<5	5949-29-1	Rat 885mg/kg (intravenous)			201-069-1

SECTION 4. FIRST AID MEASURES

General	IN ALL CASES OF DOUBT OR WHEN SYMPTOMS PERSIST, ALWAYS SEEK MEDICAL ATTENTION
Inhalation	Move affected person to fresh air. Blow nose. If recovery is not rapid, seek medical attention.
Ingestion	DO NOT INDUCE VOMITING. In case of spontaneous vomiting, be sure to that vomit can freely drain because the danger of suffocation. Only when conscious rinse mouth out. Obtain medical attention if adverse symptoms occur
Skin	Remove contaminated clothing. Wash affected area with plenty of soap and water. If irritation persists, seek medical attention. Launder clothing before reuse.
Eyes	DO NOT RUB EYES. Rinse immediately with plenty of water for at least 5 minutes while lifting the eye lids. Seek medical attention.

SECTION 5. FIRE FIGHTING MEASURES

Extinguishing Media	Noncombustible and nonflammable, but citric acid will burn or decompose in fire situation. Use extinguishing media suitable against surrounding fire or the cause of fire.
Special Fire Fighting Procedures	N/A. Dispose of contaminated water and soil according to local regulations.
Hazardous Combustion Products	Burning will produce oxides of carbon, citric acid is an organic molecule.
Protective Measures In Fire	Fire fighters should wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions In Spill	Protect eyes with goggles, avoid contact with eyes. If dust is present use respirator fitted with particulate filter.
Precautions To Protect Environment	Prevent contamination of soil, drains and surface water. Dispose spilled material according to the federal, state and local regulations.
Spill Cleanup Methods	Vacuum clean dust, take-up (shovels, brooms) or collect and place into suitable closable labeled container for disposal. Material not considered hazardous waste by RCRA (40CFR 261) dispose in approved landfill. Wash the area clean with water and detergent observing environmental requirements.

SECTION 7. HANDLING AND STORAGE

Usage Precautions	HANDLING; Product should be used in accordance with manufacturer instructions. Ensure good ventilation and local exhaust extraction in work place. Avoid contact with eyes or skin.
Storage Precautions	Store in a cool, dry, well ventilated place, in securely closed original containers. Make sure containers are not damaged. Do not store near hydrofluoric acid.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingredient Comments	No specific OES assigned, however for dusts of any kind, ensure LTEL (8hour TWA ref. period) level does not exceed 10mg/m ³ for total inhalable dust or 4mg/m ³ for respirable dust (or) as recommended in current edition of EH40
Ventilation	Provide adequate general and local exhaust ventilation
Respiration	If unable to control dust emission below recommended limits, an approved respiratory protection (EN 149 FFP) must be used at all times providing at least P2S level of protection.
Protective Gloves	When needed, use protective gloves made of: Butyl rubber, rubber (natural latex) neoprene, polyvinyl chloride (PVC).
Eye Protection	Wear approved chemical safety goggles where eye exposure is reasonably probable.
Other Protection	Wear suitable personal protective equipment suitable to the task.
Hygienic Work Practices	Skin protections apply barrier cream to hands and exposed skin. Regularly vacuum dust to minimize the potential of air-borne exposure.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	White or off-white granular, slightly wet powder
Aroma/ Taste	No aroma, or no characteristic odor, slightly acidic taste
Density/specific gravity	Bulk density less than 10lb per cubic foot Specific gravity 0.25g/ml
pH Value	Between 2 and 3 (slurry with water).
Solubility Description	Product not soluble in water.
Auto Ignition Temp	Noncombustible and nonflammable, requires external intense heat for citric acid to decompose.

SECTION 10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions of storage and use as instructed by the manufacturer.
Materials To Avoid	Bases, strong oxidizing agents, reacts with hydrofluoric acid to form silicon tetrafluoride
Hazardous Decomposition Products	As with all organic molecules burning will release carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Toxic dose LD 50	For citric acid: LD 50 Rat 885mg/kg (intravenous), Rat 11700 mg/kg (oral). LD50 for perlite N/A.
Health hazards, general	Irritating to eyes and respiratory system if inhaled as dust.
Effects of chronic exposure	Perlite is a naturally occurring volcanic glass consisting of fused sodium-potassium-aluminum silicate. Test conducted on perlite did not identify silica as being present above detection limit (0.05%). although there are not published reports of adverse effects of exposure to perlite dust, dust level should be maintained below the OSHA Permissible Exposure Limit (PEL) for perlite and respirators used when airborne dust is present.
Health warnings	This product may cause temporary skin/eye irritation.

SECTION 12. ECOLOGICAL INFORMATION

LD 50, 96 hours, fish mg/ml	Citric acid; LD50 for fish 440-706mg/l. Perlite N/A
Degradability	Citric acid biodegradable – 98% within 2 to 24 hours. Perlitic mineral is generally considered inert. Perlite has no negative ecological effect and may be used as a soil container.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods	This material is not considered hazardous waste by the RCRA (40 CFR part 261). Place waste and spillage in closed containers. Dispose in accordance with Federal, state and local regulations
------------------	--

SECTION 14. TRANSPORT INFORMATION

Special shipping information	No known shipping regulations, Shipping class 55 (no restrictions)
US D.O.T.	Not Regulated
Reportable quantities	N/A
TDG/IMO/ICAO	Not regulated
UN (/United Nations) , NA (North American) number	Not applicable

SECTION 15. REGULATORY INFORMATION

OSHA	Perlite is not considered a hazardous material or toxic substance
WHMIS	N/A
SERA	Not listed
TSCA	Not listed

SECTION 16. OTHER INFORMATION

ACGIH = American conference on governmental Industrial Hygienists
 CAS = Chemical Abstract Service
 CFR = Code of Federal Regulations
 LD = Lethal Dose
 NFPA = National Fire Protection Association
 NIOSH = National Institute of Occupational Safety and Health
 DSL/NDSL= Domestic Substances List/Non-Domestic Substance List
 EC = European Community
 EINECS = European Inventory of Existing Commercial Chemical Substances
 ELINCS = European List of Notified Chemical Substances
 EU = European Union
 GHS = Globally Harmonized System
 LC = Lethal Concentration
 NTP = National Toxicology Program
 OSHA = Occupational Safety and Health Administration
 PEL = Permissible Exposure limit
 RQ = Reportable Quantity
 SARA = Superfund Amendments and Reauthorization Act of 1986
 TLV = Threshold Limit Value
 WHMIS =Workplace Hazardous Materials Information System

The information provided in this document is correct to the best of our knowledge as of the publication date. However no warranty representation or guarantee expressed or implied with respect to this information or its completeness is intended or given. This information pertains only to the material specified and may not be valid when this material is combined with other materials or subjected to other processes. No warranty or quality specification is implied in this information. It is the responsibility of the user to handle the designated material in a safe manner and comply with all applicable local state and Federal regulations. Oil Process Systems Inc. does not accept liability for any loss or damage that may occur from the use of this information.